

Inside micrometers with interchangeable anvils

Screw thread micrometers for internal measurements of pitch diameters. The interchangeable anvils allow measurements of several kinds of screw thread.

- Measuring range: 75 - 300 mm.
- Graduation: 0.01 mm.
- Insert shaft: $\varnothing 5$ mm.
- Delivery incl. setting gauge for metric thread, 60° flank angle.



Item No.	Measuring range/mm	Accuracy mm
Inside micrometers without inserts:		
906.924	75 - 100	± 0.025
906.925	100 - 125	± 0.028
906.926	125 - 150	± 0.030
906.927	150 - 175	± 0.033
906.928	175 - 200	± 0.035
906.929	200 - 225	± 0.038
906.930	225 - 250	± 0.040
906.931	250 - 275	± 0.043
906.932	275 - 300	± 0.045

Item No.	Threads per inch
Inserts for Whitworth threads, 55° flank angle, per pair:	
906.940	60 - 48
906.941	48 - 40
906.942	40 - 32
906.944	32 - 24
906.945	24 - 18
906.946	18 - 14
906.947	14 - 10
906.948	10 - 7
906.949	7 - 4.5
906.950	4.5 - 3.5
906.951	Set 60 - 3.5

Item No.	Pitch/mm
Inserts for metric threads, 60° flank angle, per pair:	
906.933	0.4 - 0.5
906.934	0.6 - 0.9
906.935	1 - 1.75
906.936	2 - 3
906.937	3.5 - 5
906.938	5.5 - 7
906.939	Set 0.4 - 7

Item No.	Threads per inch
Inserts for UN, UNC and UNF threads, 60° flank angle, per pair:	
906.952	64 - 48
906.953	44 - 28
906.954	24 - 14
906.955	13 - 9
906.956	8 - 5
906.957	4.5 - 3.5
906.958	Set 64 - 3.5