

Control Panels for TESA MICRO-HITE Plus M 350 / 600 / 900



See opposite

12,7 x 6,4 mm main display, 6,3 x 4,2 or 3,8 x 2,9 mm auxiliary display

mm/in conversion

Via TESA MICRO-HITE plus M

IP50 (IEC 60529)



Declaration of conformity

Keypad with 42 softkeys

Bidirectional RS232, optoelectronic and Centronics

LC dual display, 128 x 63 mm in size.

- Length measurement: 7-segment/digit upper display field for values plus symbols for the functions.

- Straightness or perpendicularity measurement: display field for values plus symbols (function keys). Operator controlled operations (full dot display).

- Measured values: 7-decade display plus minus sign.

- PRESET function for entering a given value. Acoustic signal. Manual or automatic triggering of data transfer. Output of predefined reports with headers in 5 languages (plus a programmable one) using an external printer unit (A4 format).

No

=

mm

in

00760220 Power Panel for MICRO-HITE plus M with printer

0,0001 / 0,001 / 0,01

0.00001 / 0.0001 / 0.001

00760221 Power Panel for MICRO-HITE plus M

0,0001 / 0,001 / 0,01

0.00001 / 0.0001 / 0.001

OPTIONAL ACCESSORIES:

04765008 Thermal paper, 57 mm wide

04761052 Extension cable, Sub-D 9p/f to 9p/m, 2 m

04761063 Sub-D 9p/m to USB cable, 2 m

