

Lever-type digital test indicator

Lever-type digital test indicator with tolerance judgement. Suitable for measurements in both directions. Equipped with three dovetail mountings.

- Measuring range: up to 0.5 mm.
- Resolution: 0.001 mm.
- Accuracy: ± 0.02 mm.
- mm/inch conversion.
- On/off switch.
- Reset.
- Measuring force: ≤ 0.6 N.
- With dovetail joint and clamping stems $\varnothing 6$ and $\varnothing 8$ mm.
- Ruby stylus tip: $\varnothing 2$ mm.
- 230° adjustable measuring insert.
- Adjustable tolerance limits.
- Power supply: 1 battery type V357.



Item No.	Measuring range/mm	Resolution mm	Insert length/mm
907.574	0.5	0.001	20
Option: 836.535 Spare battery			

Lever-type test indicators

- Measuring range: up to 0.8 mm.
- Graduation: 0.01 or 0.002 mm.
- With dovetail joint and clamping stems $\varnothing 6$ and $\varnothing 8$ mm.
- Dial diameter: 40 mm.
- Rotatable dial.
- Stylus tip: $\varnothing 2$ mm.
- Conforms to factory standard.



907.941

Item No.	Measuring range/mm	Graduation mm	Scale numbering	Insert length/mm
907.941	0.8	0.01	0-40-0	19
907.942	0.2	0.002	0-100-0	12
Options: 909.114 Spare stylus tip for 907.941 909.115 Spare stylus tip for 907.942				

PRICE